




UNIFORM HAZARDOUS WASTE MANIFEST		1. Generator's US EPA ID No. W A D 9 8 0 7 3 8 5 4 6		Manifest Document No. 02003		2. Page 1 of 1		Information in the shaded areas is not required by Federal law.	
		3. Generator's Name and Mailing Address Alaskan Copper Works P.O. Box 3546, Seattle, WA 98124		4. Generator's Phone (206) 382-8379		5. Transporter 1 Company Name Philip Transportation & Remediation		6. US EPA ID Number CAAD063547996	
7. Transporter 2 Company Name		8. US EPA ID Number		9. Designated Facility Name and Site Address World Resources Company 8113 West Sherman Street Tolleson, Arizona 85353-4025		10. US EPA ID Number A Z D 9 8 0 7 3 5 5 0 0		11. US DOT Description (Including Proper Shipping Name, Hazard Class and ID Number)	
				12. Containers		13. Total Quantity		14. Unit Wt/Vol	
				No. Type				Waste No.	
a.		RQ, Hazardous waste, solid, n.o.s., (F006), 9, NA3077, III		003 C F		04275		P F006	
b.		RQ, Hazardous waste, solid, n.o.s., (D007), 9, NA3077, III		043 D M		29880		P D007	
c.									
d.									
J. Additional Descriptions for Materials Listed Above				K. Handling Codes for Wastes Listed Above					
15. Special Handling Instructions and Additional Information 24 Hour Emergency Response: 1-800-424-9300 CHEMTREC (Use CHEMTREC company code "WORR") (Emergency call pager # 206-648-8423) Wear gloves & goggles P.O. # M68098									
16. GENERATOR'S CERTIFICATION: I hereby declare that the contents of this consignment are fully and accurately described above by proper shipping name and are classified, packed, marked, and labeled, and are in all respects in proper condition for transport by highway according to applicable international and national government regulations. If I am a large quantity generator, I certify that I have a program in place to reduce the volume and toxicity of waste generated to the degree I have determined to be economically practicable and that I have selected the practicable method of treatment, storage, or disposal currently available to me which minimizes the present and future threat to human health and the environment; OR, if I am a small quantity generator, I have made a good faith effort to minimize my waste generation and select the best waste management method that is available to me and that I can afford.									
Printed/Typed Name GERALD A. Thompson		Signature 		Month Day Year 12/6/05					
17. Transporter 1 Acknowledgement of Receipt of Materials									
Printed/Typed Name Tom EDWARDS		Signature 		Month Day Year 12/6/05					
18. Transporter 2 Acknowledgement of Receipt of Materials									
Printed/Typed Name		Signature		Month Day Year					
19. Discrepancy Indication Space									
20. Facility Owner or Operator: Certification of receipt of hazardous materials covered by this manifest except as noted in Item 19.									
Printed/Typed Name SAMUEL BELLAMY		Signature 		Month Day Year 10/6/11					



World Resources Company

8113 West Sherman Street Tel: 602.233.9166
Tolleson, AZ 85353-4025 Fax: 623.936.9164

June 14, 2002

Mr. Gerald Thompson
Environmental Assistant
Alaskan Copper Works
P. O. Box 3546
Seattle, WA 98124-3546


Dear Mr. Thompson:

Enclosed is the appropriate copy of your company's Hazardous Waste Manifest resulting from the transfer of recyclable materials to World Resources Company.

Please note that in accordance with 40 CFR §262.40, this copy of the manifest must be retained as a record for at least three (3) years from the date the waste was accepted by the initial transporter.

If you have any questions, please feel free to give us a call.

Sincerely,
World Resources Company


Manifest Coordinator

Enclosures

UNIFORM HAZARDOUS WASTE MANIFEST		1. Generator's US EPA ID No. W.A.D. 9.8.0.7.3.5.5.4.6.0.2.0.0.3		Manifest Document No.		2. Page 1 of 1		Information in the shaded areas is not required by Federal law.					
3. Generator's Name and Mailing Address Alaskan Copper Works P.O. Box 3546, Seattle, WA 98124						A. State Manifest Document Number							
4. Generator's Phone (206) 382-8379						B. State Generator's ID							
5. Transporter 1 Company Name Philip T. ...				6. US EPA ID Number D00063507916		C. State Transporter's ID							
7. Transporter 2 Company Name				8. US EPA ID Number		D. Transporter's Phone (206) 321-1031							
9. Designated Facility Name and Site Address World Resources Company 8113 West Sherman Street Tolleson, Arizona 85353-4025						10. US EPA ID Number A.Z.D. 9.8.0.7.3.5.5.0.0		E. State Transporter's ID					
								F. Transporter's Phone					
								G. State Facility's ID					
								H. Facility's Phone 800-972-1955					
11. US DOT Description (Including Proper Shipping Name, Hazard Class and ID Number)						12. Containers		13. Total Quantity		14. Unit Wt/Vol		15. Waste No.	
a. RQ, Hazardous waste, solid, n.o.s., (F006), 9, NA3077, III						203 CF		4275		P		F006	
b. RQ, Hazardous waste, solid, n.o.s., (D007), 9, NA3077, III						243 DM		29.880		P		D007	
c.													
d.													
J. Additional Descriptions for Materials Listed Above						K. Handling Codes for Wastes Listed Above							
<small>For use by generators, transporters, and facilities to provide additional information regarding the waste and its handling. This information should be provided to the appropriate regulatory agency and to the transporter. The information should be provided in a separate section of the manifest, and should be provided in a separate section of the manifest. The information should be provided in a separate section of the manifest, and should be provided in a separate section of the manifest.</small>													
15. Special Handling Instructions and Additional Information 24 Hour Emergency Response: 1-800-424-9300 CHEMTREC (Use CHEMTREC company code "WRRR") (Emergency call pager # 206-648-8423) Wear gloves & goggles P.O. # M68098													
16. GENERATOR'S CERTIFICATION: I hereby declare that the contents of this consignment are fully and accurately described above by proper shipping name and are classified, packed, marked, and labeled, and are in all respects in proper condition for transport by highway according to applicable international and national government regulations. If I am a large quantity generator, I certify that I have a program in place to reduce the volume and toxicity of waste generated to the degree I have determined to be economically practicable and that I have selected the practicable method of treatment, storage, or disposal currently available to me which minimizes the present and future threat to human health and the environment; OR, if I am a small quantity generator, I have made a good faith effort to minimize my waste generation and select the best waste management method that is available to me and that I can afford.													
Printed/Typed Name Gordon J. ...						Signature <i>[Signature]</i>				Month Day Year 12/01/02			
17. Transporter 1 Acknowledgement of Receipt of Materials													
Printed/Typed Name T. ...						Signature <i>[Signature]</i>				Month Day Year 12/01/02			
18. Transporter 2 Acknowledgement of Receipt of Materials													
Printed/Typed Name						Signature				Month Day Year			
19. Discrepancy Indication Space													
20. Facility Owner or Operator: Certification of receipt of hazardous materials covered by this manifest except as noted in Item 19.													
Printed/Typed Name						Signature				Month Day Year			

Material Safety Data Sheet

F006 Recyclable Material (Filter Cake)

Recycler's Facility Name and Site Address:

World Resources Company

8113 West Sherman Street

Tolleson, Arizona 85353-4025

Tel.: 602/233-9166

Fax: 623/936-9164

January 2002 DLS

Call CHEMTREC only in the event of emergencies during shipping that involve a spill, leak, fire, or accident (all calls are recorded).

For emergencies during shipping in the US or Canada, day or night, call: CHEMTREC 800/424-9300.

(Use CHEMTREC Company Code "WORR".) For calls from other countries, call COLLECT: 703/527-3887.

Section 1

EPA Waste Classification: F006

Generic Name: Electroplating/Metal-Finishing Waste-water Treatment Sludge

Chemical Family: Metallic (Hydroxide) Participates

Synonym: Nonferrous Metal Hydroxide Filter Cake

Material Identification

DOT Shipping Name: RQ, Hazardous waste solid, n.o.s., (F006)

DOT Hazard Class: 9; Packing Group: III.

DOT Identification Number: NA 3077

Guide 171 of The North American Emergency Response Guidebook applies.

Section 2

Ingredient:

CAS Number:

Content%:

ACGIH-TLV:

Toxicology (rat, oral):

Copper Hydroxide

20427-59-2

0-30

1.0 mg(Cu)/m³ (dust)

LD-50 1,000 mg/kg

Nickel Hydroxide

12054-48-7

0-15

1.0 mg(Ni)/m³ (dust)

LD-50 1,500 mg/kg

Calcium Hydroxide

1305-62-0

0-15

5.0 mg(Ca)/m³ (dust)

LD-50 7,340 mg/kg

Diatomite

61790-53-2

0-10

10.0 mg/m³ (dust)

LD-50 not determined

Aluminum Hydroxide

21645-51-2

0-10

2.0 mg(Al)/m³ (dust)

LD-50 not determined

Section 3

Description: solid, clay-like, gray/green to brown, water content 30-80%

Specific Gravity: 2.5 to 3.5

Solubility: insoluble in water.

Incompatible Reactivity: none known.

Vapor Pressure: insignificant.

Stability: avoid contact with acids.

Polymerization: will not occur.

Density: 50-90 lbs./cu ft.

Physical and Reactivity Data

Boiling Point: above 2600°C

Melting Point: above 1800°C

pH: 7.0 to 10.0

Odor: nil.

Section 4

Flashpoint: nonflammable.

Special Firefighting Procedures: none.

Product Decomposition (due to fire or explosion): none.


Oxidation: non-oxidizing.

Explosion Potential: non-explosive.

Fire and Explosion Data

NFPA

Fire Diamond



Section 5

Listed Carcinogenic Components: nickel

Toxicology: see Section 2.

Route of Entry: inhalation and ingestion.

Toxicity

Section 6

Health Effects and First Aid

Inhalation: Dust may irritate mucous membranes and upper respiratory tract. Remove to fresh air and treat symptoms.

Ingestion: Rare. Induce vomiting and call a physician—but never induce vomiting or give a liquid to an unconscious person.

Eyes: Dust may irritate eyes. Wash with copious amounts of water for 15 minutes. If effects persist, call a physician.

Skin: Dust may irritate skin, causing forms of eczema. Wash with soap and water.

Long-Term: Long-term chronic over-exposure may affect the following target organs or body systems: blood; digestive; respiratory; lungs; liver; kidneys; and skin.

Comments: Special attention should be given to employees with anemia, restricted respiratory abilities, lung cancer, permanent kidney damage, mental-sensitive skin, or skin lesions.

Section 7

Precautions for Safe Handling

Handling: Good personal and industrial hygiene should always be practiced. It is recommended that personal protective equipment (PPE) be used by personnel who will come in contact with the material. The PPE should include eye protection, respirator and gloves.

Storage: Keep covered and avoid conditions where wind could cause dispersal. Do not eat, drink or smoke where material is handled, to avoid inhalation or ingestion. Store in a dry area under cover to protect from rain or snow.

Spills: Use cleaning procedures that avoid creating excessive dust. Vacuum when possible. Package material and ship to World Resources Company at the address shown above.

Section 8

Control Measures

Respiratory Protection: NIOSH-MSHA approved respirators as required.

Other Protective Equipment: coveralls are recommended but not required.

Eye Protection: safety glasses are recommended.

Hand Protection: gloves are recommended.

Section 9

Generator's Verification

This MSDS describes the recyclable material listed in the attached Manifest Number:

02003

06-5-02

↑Signature↑

↑Date↑

Alaskan Copper Works

P.O. Box 3546, Seattle, WA 98124

↑Company Name and Address↑

206-382-8379

↑Telephone↑

**WORLD RESOURCES COMPANY**

ARIZONA RECYCLING FACILITY

*In partnership with the environment***LDRN****LAND DISPOSAL RESTRICTION
NOTICE**

ISO 9001 & ISO 14001 Certified Recycling Facility

F006

A copy of this Notice must be retained by the Generator for **at least three (3) years**, pursuant to U.S. EPA Regulation 40 CFR §268.7(a)(8). Moreover, **the Generator should check** the hazardous-waste regulations of his/her own State, inasmuch as, if there is a State analogue to the federal regulation, it may require a longer retention time, such as five (5) years. It should also be noted that the federal regulation--and, typically, State analogues as well--requires the retention period to be extended further in specified cases.

To: **WORLD RESOURCES COMPANY** **8113 West Sherman Street, Tolleson AZ 85353-4025**
From: COMPANY NAME: **Alaskan Copper Works** COMPANY ADDRESS:
P.O. Box 3546, Seattle, WA 98124

MANIFEST NUMBER: **02003** DATE OF SHIPMENT: **6-6-02**

This shipment of material is subject to the land disposal restrictions of 40 CFR Part 268. The applicable land disposal restriction information, provided in accordance with 40 CFR §268.7(a)(2), is as shown in this table ↓

EPA Material Number	Treatability Group	CFR Reference for Treatment Standards
F006	non-wastewater	40 CFR §268.40

SIGNATURE:

TITLE:

Enviro. Asst.

NAME PRINTED:

Gerald A. Thompson

DATE:

06-06-02

Instructions for Completion of this Land Disposal Restriction Notice [LDRN]

This LDRN has been prepared based on a listed material--F006--as the primary designation of the material. This designation is based on information furnished by the Generator of the material. While it is believed to be accurate, it is the Generator's responsibility to determine whether his/her material is restricted from land disposal, and to correctly complete the LDR Notice [as stated in 40 CFR §268.7(a)(2)].

An F006 designation on the LDRN includes the following constituents: cadmium [D006], chromium [D007], lead [D008], silver [D011], cyanide, and nickel. However, the designation does not include arsenic [D004], barium [D005], mercury [D009], or selenium [D010]. If your F006 material contains any of those four constituents not included in the F006 designation, then use the following instructions.

In determining the need for any additional entries on the LDRN for the F006 material, the levels of arsenic, barium, mercury and selenium must be examined to determine if the levels equal or exceed the threshold concentrations of constituents for the Toxicity Characteristic limit as identified in 40 CFR §261.24 (Table 1), as shown in the left-hand column of the table below [as stated in 40 CFR §268.9].

If (after testing or based upon the generator's knowledge of the material) each metal level does not equal the Toxicity Characteristic level shown below, then *no additional entry* is required on the LDR Notice. If the level is known to be or determined to be equal to or above the limit shown below for any of these metals, then the appropriate information corresponding to that individual metal (in the right-hand column below) *must be added* to the LDR Notice.

REFERENCE INFORMATION TOXICITY CHARACTERISTIC		APPROPRIATE ENTRY ON LDR NOTICE		
Metal	Concentration Level	EPA Material Number	Treatability Group	CFR Reference for Treatment Standards
ARSENIC	5.0 mg/l	D004	non-wastewater	40 CFR §268.40
BARIUM	100 mg/l	D005	non-wastewater	40 CFR §268.40
MERCURY	.02 mg/l	D009	non-wastewater	40 CFR §268.40
SELENIUM	1.0 mg/l	D010	non-wastewater	40 CFR §268.40

AZF010\1F1 ©1994 by WORLD RESOURCES COMPANY. All rights reserved. Revised 11/08/98, 08/16/00, 08/01/01. This Revision: 11/09/01.

F006 GENERATORS

AKC-0017152

Material Safety Data Sheet

D007 Recyclable Material (Filter Cake)

Recycler's Facility Name and Site Address:

World Resources Company

8113 West Sherman Street
Tolleson, Arizona 85353-4025
Tel.: 602/233-9166 Fax: 623/936-9164

January 2002 DLS

Call CHEMTREC only in the event of emergencies during shipping that involve a spill, leak, fire, or accident (all calls are recorded).

For emergencies during shipping in the US or Canada, day or night, call: **CHEMTREC 800/424-9300**.

(Use CHEMTREC Company Code "WRRR".)
For calls from other countries, call COLLECT: 703/527-3887.

Section 1

EPA Waste Classification: D007
Generic Name: Chromium-Bearing Filter Cake
Chemical Family: Metallic (Hydroxide) Participates
Synonym: Nonferrous Metal Hydroxide Filter Cake

DOT Shipping Name: RQ, Hazardous waste solid, n.o.s., (D007)
DOT Hazard Class: 9; **Packing Group:** III.
DOT Identification Number: NA 3077
Guide 171 of The North American Emergency Response Guidebook applies.

Material Identification

Section 2

Ingredient:	CAS Number:	Content%:	ACGIH-TLV:	Toxicology (rat, oral):
Copper Hydroxide	20427-59-2	0-30	1.0 mg(Cu)/m ³ (dust)	LD-50 1,000 mg/kg
Nickel Hydroxide	12054-48-7	0-15	1.0 mg(Ni)/m ³ (dust)	LD-50 1,500 mg/kg
Calcium Hydroxide	1305-62-0	0-15	5.0 mg(Ca)/m ³ (dust)	LD-50 7,340 mg/kg
Diatomite	61790-53-2	0-10	10.0 mg/m ³ (dust)	LD-50 not determined
Chromic Hydroxide	1308-58-1	1-20	0.05 mg(Cr)/m ³ (dust)	LD-50 not determined

Hazardous Ingredients

Section 3

Description: solid, clay-like, gray/green to brown, water content 30-80%
Specific Gravity: 2.5 to 3.5
Solubility: insoluble in water.
Incompatible Reactivity: none known.

Vapor Pressure: insignificant.
Stability: avoid contact with acids.
Polymerization: will not occur.
Density: 50-90 lbs./cu ft.

Physical and Reactivity Data

Boiling Point: above 2600°C
Melting Point: above 1800°C
pH: 7.0 to 10.0
Odor: nil.


Section 4

Flashpoint: nonflammable.
Special Firefighting Procedures: none.
Product Decomposition (due to fire or explosion): none.

Oxidation: non-oxidizing.
Explosion Potential: non-explosive.

Fire and Explosion Data

NFPA
Fire Diamond



Section 5

Listed Carcinogenic Components: nickel, chromium **Toxicology:** see Section 2. **Route of Entry:** inhalation and ingestion.

Toxicity

Section 6

Health Effects and First Aid

Inhalation: Dust may irritate mucous membranes and upper respiratory tract. Remove to fresh air and treat symptoms.
Ingestion: Rare. Induce vomiting and call a physician—but never induce vomiting or give a liquid to an unconscious person.
Eyes: Dust may irritate eyes. Wash with copious amounts of water for 15 minutes. If effects persist, call a physician.
Skin: Dust may irritate skin, causing forms of eczema. Wash with soap and water.
Long-Term: Long-term chronic over-exposure may affect the following target organs or body systems: blood; digestive; respiratory; lungs; liver; kidneys; and skin.
Comments: Special attention should be given to employees with anemia, restricted respiratory abilities, lung cancer, permanent kidney damage, mental-sensitive skin, or skin lesions.

Section 7

Precautions for Safe Handling

Handling: Good personal and industrial hygiene should always be practiced. It is recommended that personal protective equipment (PPE) be used by personnel who will come in contact with the material. The PPE should include eye protection, respirator and gloves.
Storage: Keep covered and avoid conditions where wind could cause dispersal. Do not eat, drink or smoke where material is handled, to avoid inhalation or ingestion. Store in a dry area under cover to protect from rain or snow.
Spills: Use cleaning procedures that avoid creating excessive dust. Vacuum when possible. Package material and ship to World Resources Company at the address shown above.

Section 8

Control Measures

Respiratory Protection: NIOSH-MSHA approved respirators as required.
Other Protective Equipment: coveralls are recommended but not required.

Eye Protection: safety glasses are recommended.
Hand Protection: gloves are recommended.

Section 9

Generator's Verification

This MSDS describes the recyclable material listed in the attached Manifest Number:

02003

↑ Signature ↑

06-0502

↑ Date ↑

Alaskan Copper Works
P.O. Box 3546, Seattle, WA 98124

↑ Company Name and Address ↑

206-382-8379

↑ Telephone ↑

**WORLD RESOURCES COMPANY**

ARIZONA RECYCLING FACILITY

*In partnership with the environment***LDRN**
LAND DISPOSAL RESTRICTION
NOTICE

ISO 14001 Certified Recycling Facility

D007

A copy of this Notice must be retained by the Generator for **at least three (3) years**, pursuant to U.S. EPA Regulation 40 CFR §268.7(a)(8). Moreover, **the Generator should check** the hazardous-waste regulations of his/her own State, inasmuch as, if there is a State analogue to the federal regulation, it may require a longer retention time, such as five (5) years. It should also be noted that the federal regulation--and, typically, State analogues as well--requires the retention period to be extended further in specified cases.

TO: **WORLD RESOURCES COMPANY****8113 West Sherman Street, Tolleson AZ 85353-4025**

FROM:

Alaskan Copper Works**P.O. Box 3546, Seattle, WA 98124**

[COMPANY NAME]

[COMPANY ADDRESS]

MANIFEST
NUMBER:**02003**DATE OF
SHIPMENT:**6-5-02**

This shipment of material is subject to the land disposal restrictions of 40 CFR Part 268. The applicable land disposal restriction information, provided in accordance with 40 CFR §268.7(a)(2), is as shown in this table ↓

EPA Material Number	Treatability Group	CFR Reference for Treatment Standards
D007	non-wastewater	40 CFR §268.40

SIGNATURE:

TITLE:

Enviro. Asst.NAME
PRINTED:**GERARD A. Thompson**

DATE:

06-5-02**Instructions****for the Completion of this
Land Disposal Restriction Notice
(D007 LDRN)**

This LDRN has been prepared based on a listed material--D007--as the primary designation of the material. This designation is based on information furnished by the Generator of the material. While it is believed to be accurate, it is the Generator's responsibility to determine whether his/her material is restricted from land disposal, and to correctly complete the LDR Notice [as stated in 40 CFR §268.7(a)(2)].

If your material is described by additional "D" characteristic EPA waste codes, then they must each be included on the LDR Notice.

MATERIAL IDENTIFICATION

DOT BASIC SHIPPING DESCRIPTION AND TECHNICAL NAME:
Hazardous waste, solid, n.o.s., (F006), 9. NA3077, III

NORTH AMERICAN
EMERGENCY
RESPONSE

TAKEN FROM GUIDE 171 OF THE NORTH AMERICAN EMERGENCY RESPONSE GUIDEBOOK

(Underlined text applies directly to the material listed above)

POTENTIAL HAZARDS

FIRE OR EXPLOSION

1. Some may burn, but none ignite readily.
2. Some may polymerize (P) explosively when heated or involved in a fire.
3. Containers may explode when heated.
4. Some may be transported hot.

HEALTH

1. Inhalation of material may be harmful.
2. Contact may cause burns to skin and eyes.
3. Inhalation of Asbestos dust may have a damaging effect on the lungs.
4. Fire may produce irritating, corrosive and/or toxic gases.
5. Runoff from fire control may cause pollution.

PUBLIC SAFETY

1. CALL CHEMTREC at 1-800-424-9300 FOR EMERGENCY ASSISTANCE (Use CHEMTREC Company Code "WORR").
2. Isolate spill or leak area immediately for at least 10 to 25 meters (30-80 feet) in all directions.
3. Keep unauthorized personnel away.
4. Stay upwind.

PROTECTIVE CLOTHING

1. Wear positive pressure self-contained breathing apparatus (SCBA).
2. Structural firefighters' protective clothing will only provide limited protection.

EVACUATION

Fire

1. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

EMERGENCY RESPONSE

FIRE

Small Fires

1. Dry chemical, CO₂, water spray or regular foam.

Large Fires:

1. Water spray, fog or regular foam.
2. Move containers from fire area if you can do it without risk.
3. Do not scatter spilled material with high pressure water streams.
4. Dike fire-control water for later disposal.

Fire Involving Tanks:

1. Cool containers with flooding quantities of water until well after fire is out.
2. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
3. ALWAYS stay away from the ends of tanks.

SPILL OR LEAK

1. Do not touch or walk through spilled material.
2. Stop leak if you can do it without risk.
3. Prevent dust cloud.
4. Avoid inhalation of asbestos dust.

Small Dry Spills

1. With clean shovel, place material into clean, dry container and cover loosely; move containers from spill area.

Small Spills

1. Take up with sand or other noncombustible absorbent material and place into containers for later disposal.

Large Spills

1. Dike far ahead of liquid spill for later disposal.
2. Cover powder spill with plastic sheet or tarp to minimize spreading.
3. Prevent entry into waterways, sewers, basements or confined areas.

FIRST AID

1. Move victim to fresh air.
2. Call emergency medical care.
3. Apply artificial respiration if victim is not breathing.
4. Administer oxygen if breathing is difficult.
5. Remove and isolate contaminated clothing and shoes.
6. In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
7. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

MATERIAL IDENTIFICATION

DOT BASIC SHIPPING DESCRIPTION AND TECHNICAL NAME:
Hazardous waste, solid, n.o.s., (D007), 9, NA3077, III

NORTH AMERICAN
EMERGENCY
RESPONSE

TAKEN FROM GUIDE 171 OF THE NORTH AMERICAN EMERGENCY RESPONSE GUIDEBOOK (Underlined text applies directly to the material listed above)

POTENTIAL HAZARDS

FIRE OR EXPLOSION

1. Some may burn, but none ignite readily.
2. Some may polymerize (P) explosively when heated or involved in a fire.
3. Containers may explode when heated.
4. Some may be transported hot.

HEALTH

1. Inhalation of material may be harmful.
2. Contact may cause burns to skin and eyes.
3. Inhalation of Asbestos dust may have a damaging effect on the lungs.
4. Fire may produce irritating, corrosive and/or toxic gases.
5. Runoff from fire control may cause pollution.

PUBLIC SAFETY

1. CALL CHEMTREC at 1-800-424-9300 FOR EMERGENCY ASSISTANCE (Use CHEMTREC Company Code "WQRR").
2. Isolate spill or leak area immediately for at least 10 to 25 meters (30-80 feet) in all directions.
3. Keep unauthorized personnel away.
4. Stay upwind.

PROTECTIVE CLOTHING

1. Wear positive pressure self-contained breathing apparatus (SCBA).
2. Structural firefighters' protective clothing will only provide limited protection.

EVACUATION

Fire

1. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

FIRE

EMERGENCY RESPONSE

Small Fires

1. Dry chemical, CO₂, water spray or regular foam.

Large Fires:

1. Water spray, fog or regular foam.
2. Move containers from fire area if you can do it without risk.
3. Do not scatter spilled material with high pressure water streams.
4. Dike fire-control water for later disposal.

Fire Involving Tanks:

1. Cool containers with flooding quantities of water until well after fire is out.
2. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
3. ALWAYS stay away from the ends of tanks.

SPILL OR LEAK

1. Do not touch or walk through spilled material.
2. Stop leak if you can do it without risk.
3. Prevent dust cloud.
4. Avoid inhalation of asbestos dust.

Small Dry Spills

1. With clean shovel, place material into clean, dry container and cover loosely; move containers from spill area.

Small Spills

1. Take up with sand or other noncombustible absorbent material and place into containers for later disposal.

Large Spills

1. Dike far ahead of liquid spill for later disposal.
2. Cover powder spill with plastic sheet or tarp to minimize spreading.
3. Prevent entry into waterways, sewers, basements or confined areas.

FIRST AID

1. Move victim to fresh air.
2. Call emergency medical care.
3. Apply artificial respiration if victim is not breathing.
4. Administer oxygen if breathing is difficult.
5. Remove and isolate contaminated clothing and shoes.
6. In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
7. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

WORLD RESOURCES
11:55AM 06/11/2002
GROSS 1154 lb
TARE 104 lb
NET 1050 lb

WORLD RESOURCES
11:56AM 06/11/2002
GROSS 1040 lb
TARE 104 lb
NET 936 lb

WORLD RESOURCES
11:57AM 06/11/2002
GROSS 737 lb
TARE 104 lb
NET 633 lb

WORLD RESOURCES
11:59AM 06/11/2002
GROSS 1336 lb
TARE 104 lb
NET 1232 lb

WORLD RESOURCES
12:02PM 06/11/2002
GROSS 437 lb
TARE 52 lb
NET 385 lb

WORLD RESOURCES
12:07PM 06/11/2002
GROSS 483 lb
TARE 52 lb
NET 431 lb

WORLD RESOURCES
12:08PM 06/11/2002
GROSS 1642 lb
TARE 104 lb
NET 1538 lb

WORLD RESOURCES
12:10PM 06/11/2002
GROSS 1311 lb
TARE 104 lb
NET 1207 lb

WORLD RESOURCES
12:11PM 06/11/2002
GROSS 1287 lb
TARE 104 lb
NET 1183 lb

WORLD RESOURCES
12:12PM 06/11/2002
GROSS 1238 lb
TARE 104 lb
NET 1134 lb

WORLD RESOURCES
12:13PM 06/11/2002
GROSS 1307 lb
TARE 104 lb
NET 1203 lb

WORLD RESOURCES
12:14PM 06/11/2002
GROSS 1415 lb
TARE 104 lb
NET 1311 lb
WORLD RESOURCES
12:15PM 06/11/2002
GROSS 1674 lb
TARE 104 lb
NET 1570 lb
WORLD RESOURCES
12:18PM 06/11/2002
GROSS 880 lb
TARE 104 lb
NET 776 lb
WORLD RESOURCES
12:19PM 06/11/2002
GROSS 1644 lb
TARE 104 lb
NET 1540 lb
WORLD RESOURCES
12:20PM 06/11/2002
GROSS 751 lb
TARE 104 lb
NET 647 lb
WORLD RESOURCES
12:22PM 06/11/2002
GROSS 1388 lb
TARE 104 lb
NET 1284 lb
WORLD RESOURCES
12:23PM 06/11/2002
GROSS 1692 lb
TARE 104 lb
NET 1588 lb
WORLD RESOURCES
12:24PM 06/11/2002
GROSS 1588 lb
TARE 104 lb
NET 1484 lb
WORLD RESOURCES
12:26PM 06/11/2002
GROSS 1611 lb
TARE 104 lb
NET 1507 lb
WORLD RESOURCES
12:27PM 06/11/2002
GROSS 1644 lb
TARE 104 lb
NET 1540 lb
WORLD RESOURCES
12:29PM 06/11/2002
GROSS 1929 lb
TARE 104 lb
NET 1825 lb
WORLD RESOURCES
12:30PM 06/11/2002
GROSS 1004 lb
TARE 52 lb
NET 952 lb
• ACCUM 27057 lb
06/11/2002 12:30PM

13.53
1075

WORLD RESOURCES
12:32PM 06/11/2002
GROSS 1622 lb
TARE 77 lb
NET 1545 lb
WORLD RESOURCES
12:33PM 06/11/2002
GROSS 1526 lb
TARE 77 lb
NET 1449 lb
WORLD RESOURCES
12:34PM 06/11/2002
GROSS 1089 lb
TARE 77 lb
NET 1012 lb
ACCUH 4006 lb
06/11/2002 12:34PM

2.00
Tons